




SOLID ROUND BAR

Group No.:

RB-G1




SECTION NO.	D (mm)	WEIGHT (kg/m)	AP (mm)	ALLOY TYPE & TEMPER
1600	4.78	0.049	15.02	6063-T5
1618	5.00	0.053	15.71	6063-T5
1648	5.00	0.053	15.71	6060-T6
1601	5.50	0.065	17.28	6063-T5
1622	6.30	0.085	19.79	6063-T5
1684	6.35	0.086	19.95	6082-T6511
1801	6.45	0.091	20.26	6063-T5
1625	7.25	0.112	22.78	6063-T5
1603	7.92	0.132	24.88	6063-T5
1627	8.00	0.136	25.13	6063-T5
1673	8.00	0.136	25.13	6061-T6
1647	8.00	0.136	25.13	6060-T6
1623	8.33	0.148	26.17	6063-T5
1694	9.00	0.173	28.27	6063-T4
1683	9.52	0.193	29.92	6061-T6511
1604	9.53	0.193	29.94	6063-T5
1675	10.00	0.213	31.42	6061-T6
1664	10.00	0.213	31.42	6060-T6
1624	10.33	0.227	32.45	6063-T5
1643	11.10	0.267	34.87	6063-T5
1619	11.50	0.282	36.13	6063-T5
1646	12.00	0.305	37.70	6060-T6
1620	12.70	0.344	39.90	6063-T5
1649	12.70	0.344	39.90	6061-T6
1638	15.88	0.537	49.89	6063-T5



SOLID ROUND BAR

Group No.:
RB-G1




SECTION NO.	D (mm)	WEIGHT (kg/m)	AP (mm)	ALLOY TYPE & TEMPER
1665	15.88	0.537	49.89	6061-T6 / 6082-T6
1808	16.00	0.616	50.27	6063-T5
1607	19.05	0.772	59.85	6063-T5
1657	19.05	0.773	59.85	6061-T6511
1686	20.00	0.852	62.83	6082-T6511
1628	21.00	0.940	65.97	6063-T5
1640	22.23	1.053	69.84	6063-T5
1658	22.23	1.053	69.84	6061-T6511
1609	25.40	1.374	79.80	6063-T5
1650	25.40	1.375	79.80	6061-T6511
1670	28.58	1.740	89.79	6082-T6
1676	30.00	1.917	94.25	6082-T6
1639	31.75	2.148	99.75	6063-T5
1659	31.75	2.148	99.75	6061-T6511
1660	34.93	2.599	109.74	6061-T6511
1674	35.00	2.610	109.96	6061-T6
1631	38.10	3.093	119.69	6063-T5
1651	38.10	3.093	119.69	6061-T6511
1621	40.00	3.409	125.66	6063-T5
1807	40.00	3.409	125.66	6082-T6
1672	40.00	3.409	125.66	6060-T66
1689	41.28	3.629	129.67	6082-T6511
1671	42.00	3.758	131.95	6061-T6
1634	44.45	4.209	139.64	6063-T5
1806	44.45	4.209	139.64	6082-T6



SOLID ROUND BAR

Group No.:
RB-G1




SECTION NO.	D (mm)	WEIGHT (kg/m)	AP (mm)	ALLOY TYPE & TEMPER
1652	44.45	4.209	138.64	6061-T6511
1682	45.00	4.314	141.37	6061-T6
1681	47.63	4.833	149.63	6082-T6
1677	50.00	5.326	157.08	6082-T6
1613	50.80	5.493	159.59	6063-T5
1654	50.80	5.498	159.59	6061-T6511
1692	53.00	5.985	166.50	6061-T6
1661	53.98	6.208	169.58	6061-T6511
1635	57.15	6.958	179.54	6063-T5
1653	57.15	6.958	179.54	6061-T6511
1629	59.70	7.593	187.55	6063-T5
1678	60.00	7.670	188.50	6082-T6
1615	63.50	8.618	199.49	6063-T5
1655	63.50	8.591	199.49	6061-T6511
1630	66.00	9.280	207.35	6063-T5
1690	66.68	9.471	209.47	6082-T6511
1691	67.00	9.564	210.49	6061-T6
1641	69.85	10.395	219.44	6063-T5
1662	69.85	10.395	219.44	6061-T6511
1617	76.20	12.403	239.39	6063-T5
1656	76.20	12.371	239.39	6061-T6511
1679	80.00	13.635	251.33	6082-T6
1685	82.55	14.518	259.34	6082-T6511
1633	82.55	14.518	259.34	6063-T5
1687	85.00	15.393	267.04	6061-T6511



SOLID ROUND BAR

Group No.:
RB-G1



SECTION NO.	D (mm)	WEIGHT (kg/m)	AP (mm)	ALLOY TYPE & TEMPER
1636	88.90	16.838	279.29	6063-T5
1663	88.90	16.838	279.29	6061-T6511
1693	90.00	17.257	288.74	6082-T6
1667	95.00	19.228	298.45	6061-T6
1645	95.25	19.329	299.24	6061-T6
1680	100.00	21.305	314.16	6082-T6
1632	101.60	21.992	319.19	6063-T5
1668	101.60	21.992	319.19	6061-T6
1637	107.95	24.827	339.13	6063-T5
1669	107.95	24.827	339.13	6061-T6
1699	110.00	25.779	345.58	6082-T6511
1696	114.30	27.834	359.08	6082-T6511
1642	114.60	27.980	360.03	6063-T5
1697	120.65	31.012	379.03	6082-T6511
1695	127.00	34.366	398.98	6082-T6511
1698	133.35	37.888	418.93	6082-T6511
1802	139.70	41.579	438.88	6061-T6
1803	146.00	45.414	458.67	6061-T6
1800	152.40	49.482	478.78	6061-T6