



'T' BARS / 'T' BEAM


Group No.:

IB-G1

Legend:

6060 / 6063 = r0.3

6061 / 6082 = r0.5



SECTION NO.	A (mm)	B (mm)	R (mm)	T (mm)	t (mm)	WEIGHT (kg/m)	AP (mm)	ALLOY TYPE & TEMPER
5402	12.00	9.10	-	1.30	1.30	0.107	62.05	6060-T6
5410	50.80	76.20	3.00	6.00	6.00	2.718	336.73	6061-T6
5550	50.80	53.96	0.75	1.58	1.58	0.654	305.64	6063-T5
5408	50.80	101.60	5.00	6.00	6.00	3.169	384.10	6061-T6
5557	50.80	127.00	6.00	6.00	6.00	3.608	433.18	6061-T6
5414	76.20	101.60	9.53	4.76	4.76	3.367	480.40	6061-T6
5407	76.20	101.60	9.53	6.35	4.78	3.987	480.35	6061-T6511
5409	76.20	152.40	6.00	8.00	8.00	6.350	581.58	6063-T5
5411	76.20	177.80	5.00	9.525	6.35	6.729	637.40	6061-T6
5404	88.90	127.00	11.10	7.92	6.35	6.023	576.13	6061-T6511
5406	88.90	152.40	11.13	9.53	6.35	7.178	626.88	6061-T6511
5401	100.00	150.00	3.00	5.00	4.50	4.442	684.82	6063-T5
5403	101.60	101.60	11.10	7.92	6.35	6.128	576.13	6061-T6511
5405	101.60	152.40	11.10	9.53	7.14	8.118	676.15	6061-T6511
5412	152.40	152.40	-	9.53	9.53	11.320	892.77	6061-T6511