




SOLID SQUARE BAR

Group No.:
SB-G1



Legend:

6060/6063 = r0.3


6061/6082 = r0.5

SECTION NO.	A (mm)	WEIGHT (kg/m)	AP (mm)	ALLOY TYPE & TEMPER
1751	6.35	0.109	24.54	6061-T6511
1732	6.35	0.109	24.88	6063-T5
1734	8.00	0.173	31.14	6061-T6
1725	9.53	0.247	37.60	6061-T6
1701	9.53	0.247	37.60	6063-T5
1383	9.85	0.276	38.88	6063-T5
1717	10.00	0.271	39.48	6060-T6
1728	12.70	0.437	49.94	6082-T6
1708	12.70	0.437	50.28	6063-T5
1709	15.88	0.682	62.92	6063-T5
1742	15.88	0.683	62.64	6061-T6511
1729	19.05	0.984	75.34	6082-T6
1713	19.05	0.984	75.68	6063-T5
1730	22.23	1.340	88.06	6061-T6
1723	25.40	1.750	100.74	6061-T6511
1710	25.40	1.750	101.08	6061-T6511
1748	25.60	1.777	101.54	6061-T6
1739	30.00	2.440	119.14	6082-T6
1718	31.75	2.734	126.14	6061-T6
1743	35.00	3.323	139.48	6082-T6511
1722	38.10	3.937	151.54	6061-T6511
1716	38.10	3.958	151.88	6061-T6511
1736	40.00	4.340	159.14	6082-T6
1727	44.45	5.359	176.94	6061-T6
1711	44.45	5.359	177.28	6063-T5
1737	50.00	6.781	199.14	6082-T6
1721	50.80	7.000	202.34	6061-T6511
1712	50.80	7.000	202.68	6063-T5
1733	57.15	8.860	227.74	6061-T6



SOLID SQUARE BAR

Group No.:
SB-G1



Legend:

6060/6063 = r0.3


6061/6082 = r0.5

SECTION NO.	A (mm)	WEIGHT (kg/m)	AP (mm)	ALLOY TYPE & TEMPER
1738	60.00	9.765	239.14	6082-T6
1719	63.50	10.937	253.14	6061-T6511
1740	66.68	12.060	265.86	6082-T6
1731	70.00	13.291	279.14	6061-T6
1720	76.20	15.750	303.94	6061-T6511
1707	76.20	15.750	304.28	6063-T5
1741	82.55	18.485	329.34	6082-T6
1724	88.90	21.438	354.74	6061-T6511
1714	88.90	21.438	355.08	6063-T5
1749	100.00	27.126	399.14	6082-T6511
1715	101.60	28.001	405.54	6063-T5
1746	101.60	28.001	405.54	6061-T6
1744	114.30	35.438	456.34	6082-T6511
1747	127.00	43.751	507.14	6061-T6
1745	130.00	45.843	519.14	6061-T6511



SOLID SQUARE BAR WITH RADIUS

Group No.:
SB-G2



SECTION NO.	A (mm)	R (mm)	WEIGHT (kg/m)	AP (mm)	ALLOY TYPE & TEMPER
1754	62.23	7.62	10.370	235.84	6061-T6511